

## 40 Feet Sidewall Semi-trailer Specification List

Tank trailer specification			
1	Description	Heavy Duty Cargo Sidewall Trailer.	
2	Function	Transport container, loose cargo, bagged cement, bulk rice, etc.	
3	Overall dimensions	13000×2550×2970 mm ( L×W×H ) (Approx., based on final design drawings.)	
4	Curb weight	In accordance with design drawings, with heavy-duty structural design.	
5	Material	Carbon steel,Q355B.	
6	Payload	50 tons.	
7	Fifth-wheel height	1350mm (Generally within 1250 - 1450 mm; precise dimensions required based on customer's truck head.)	
8	Chassis	Top flange	Thickness: 14mm
		Middle flange	Thickness: 8mm
		Bottom flange	Thickness: 16mm
		Boundary flange	Thickness: 14mm (Channel steel)
9	Platform	Thickness 3 mm & checkered steel plate.	
10	Sidewall board	60cm height, detachable type.	
Main parts specification			
11	Suspension	Mechanical suspension,leaf springs,16mm×90mm,10pcs	
12	Axle	13T Brand TSV with ABS and automatic slack adjusters & 3 units. (BPW/Fuwa/L1 brands optional)	
13	Tire	12R22.5 & 12 units (Tubeless type). (Triangle/Doublecoin/Linglong/Chaoyang brands optional)	
14	Rim	9.00 & 12 units, high-strength iron.	
15	King pin	50#(2") or 90# (3.5") , standard bolt type & JOST brand	
16	Landing gear	Capacity 28T, JOST brand, Model A300C	
17	Spare wheel carrier	2 units	
18	Twist lock	12 units (Suitable for 20ft / 40ft containers)	
19	Lash hook	2× 12mm diameter lash hooks at the rear; 12mm diameter lash hooks fitted on side rails with 500mm spacing.	

Tianjin Sailing Vehicle Co., Ltd.  
天津塞羚汽车有限公司



SAILING VEHICLE

# 天津塞羚汽车有限公司 TIANJIN SAILING VEHICLE CO., LTD.

No.6975, Asia Road, Dongjiang Bonded Port Area, Tianjin City, China.

Tel: +86 17303276268

Web: www.sailingvehicle.com

			Heavy-duty construction. Available in large quantities.
20	Lashing Winch		Available in large quantities.
21	Mud guard plate		Integrated design plate,heavy-duty design.
22	Electric system		24V, 7-pin socket, National standard.
23	Lights		LED lights with protection. Side/rear/stop/indicator/parking/fog/reverse/clearance lights etc.
24	Reverse buzzer		1 unit.
25	Painting	Primer layer	One coat of anti-corrosive paint.
		Final coat	Two coats of finish paint.
		Color	As per customer's requirements.
26	Delivery		Spray wax before departure and cover with tarpaulin for protection.
<b>Other equipment</b>			
<ol style="list-style-type: none"> <li>1.One heavy-duty tool box, maximum possible size.</li> <li>2.Two sets of 8KG fire extinguishers with boxes.</li> <li>3.One set of anti-static grounding strap.</li> <li>4.All other necessary accessories.</li> <li>5.Provide sufficient spare parts for the client, such as joints, hinges, lights, hooks, winches, etc.</li> </ol>			

*Thank for checking!*

