



SAILING VEHICLE

天津塞羚汽车有限公司 TIANJIN SAILING VEHICLE CO., LTD.

No.6975, Asia Road, Dongjiang Bonded Port Area, Tianjin City, China.

Tel: +86 17303276268

Web: www.sailingvehicle.com

40 Feet Skeleton Trailer Specification List

Tank trailer specification			
1	Description	20Feet Skeleton Type Semi-trailer.	
2	Function	Exclusively designed for transporting ISO standard 20ft and 40ft containers.	
3	Overall dimensions	12330×2550×1560 mm (L×W×H) (Approx., based on final design drawings.)	
4	Curb weight	In accordance with design drawings, with lightweight optimized structural design.	
5	Material	Carbon steel,Q355B.	
6	Payload	45 tons.	
7	Fifth-wheel height	1350mm (Generally within 1250 - 1450 mm; precise dimensions required based on customer's truck head.)	
8	Chassis	Top flange	Thickness: 14mm
		Middle flange	Thickness: 8mm
		Bottom flange	Thickness: 16mm
		Boundary flange	Thickness: 14mm (Channel steel)
9	Cross members	High-strength steel cross beams, spaced at approx. 600mm intervals. Open skeleton design - no floor deck plate.	
Main parts specification			
10	Suspension	Mechanical suspension,leaf springs,16mm×90mm,10pcs	
11	Axle	13T Brand TSV with ABS and automatic slack adjusters & 3 units. (BPW/Fuwa/L1 brands optional)	
12	Tire	12R22.5 & 12 units (Tubeless type). (Triangle/Doublecoin/Linglong/Chaoyang brands optional)	
13	Rim	9.00 & 12 units, high-strength iron.	
14	King pin	50#(2") or 90# (3.5") , standard bolt type & JOST brand	
15	Landing gear	Capacity 28T, JOST brand, Model A300C	
16	Spare wheel carrier	2 units	
17	Twist lock	12 units (Suitable for 20ft / 40ft containers)	
18	Container support pads	Rubber-lined steel pads at all container contact points to prevent	

Tianjin Sailing Vehicle Co., Ltd.
天津塞羚汽车有限公司



SAILING VEHICLE

天津塞羚汽车有限公司 TIANJIN SAILING VEHICLE CO., LTD.

No.6975, Asia Road, Dongjiang Bonded Port Area, Tianjin City, China.

Tel: +86 17303276268

Web: www.sailingvehicle.com

			sliding and surface damage.
19	Container compatibility		20ft x 1 unit; 20ft x 2 units (tandem); 40ft x 1 unit; 40ft HC x 1 unit.
20	Mud guard plate		Integrated design plate,heavy-duty design.
21	Electric system		24V, 7-pin socket, National standard.
22	Lights		LED lights with protection. Side/rear/stop/indicator/parking/fog/reverse/clearance lights etc.
23	Reverse buzzer		1 unit.
24	Painting	Primer layer	One coat of anti-corrosive paint.
		Final coat	Two coats of finish paint.
		Color	As per customer's requirements.
25	Delivery		Spray wax before departure and cover with tarpaulin for protection.

Other equipment

- 1.One heavy-duty tool box, maximum possible size.
- 2.Two sets of 8KG fire extinguishers with boxes.
- 3.One set of anti-static grounding strap.
- 4.All other necessary accessories.
- 5.Provide sufficient spare parts for the client, such as joints, hinges, lights, hooks, winches, etc.

Thanks for checking!

